

# MAXIMA AUTO LPG 5W-30

Synthetic Motor Oil for Next-Generation LPG Fueled Engines

## Description

It is a synthetic motor oil formulated specifically for LPG vehicles, which is produced by adding high-performance additives to high technology synthetic base oils.

## Areas of Use

It can be used in LPG-reformed passenger cars and light commercial vehicles with next-generation engines, and in vehicles with factory-installed LPG fuel systems.

## Characteristics and Benefits

- Prevents temperature caused by overheating in engines operating with LPG.
- Resistant to high engine temperature thanks to its synthetic formula.
- Its special formula provides reduction control with less evaporation loss. It minimizes the abrasion by reducing the friction during the start-up.
- Extends engine life by providing superior protection against wear and corrosion.
- Increases engine efficiency and provides high engine power.
- Provides faster start-up and protection.

## Specifications Met and Approvals Obtained

API SL/CF ACEA A3/B4

## Typical Characteristics\*

SAE Viscosity Class		5W-30
Density, @ 15 °C, kg/m <sup>3</sup>	ASTM D-4052	0.853
Flash Point, COC, °C	ASTM D-92	230
Viscosity, 40 °C, mm <sup>2</sup> /s		67.2
Viscosity, 100 °C, mm <sup>2</sup> /s	ASTM D 445	11.9
Viscosity Index	ASTM D-2270	160
Pour Point, °C	ASTM D-97	-41

\* Values shown may differ between productions.