

# MAXIMA K 5W-30

Full-Synthetic Gasoline Motor Oil

## Description

This is new-generation motor oil, which is formulated with synthetic base oils and special additives, and which produced for vehicle motors containing DPF and SCR and having emission-reducing systems.

## Applications

Maxima K 5W-30 for diesel passenger and light commercial vehicle motors equipped with DPF and SCR exhaust emission systems demanding motor oil with an ACEA C2 or C3 performance level and gasoline vehicle motors with catalytic converters. This is specially developed for KIA branded vehicles.

## Benefits

- Ensures high motor performance.
- Extends the life of the exhaust emission systems.
- Contributes to the low emission production and protects the environment.
- Reduces the generation of the residue and dropping and ensures the motor to remain clean.
- Helps the fuel saving.

## Performance

ACEA C2/C3, API SN

## Typical Specifications\*

SAE Viscosity Grade		5W-30
Density, @ 15 °C, kg/m <sup>3</sup>	ASTM D-4052	0,86
Flash Point, COC, °C	ASTM D-92	220
Viscosity, 40 °C, mm <sup>2</sup> /s	ASTM D 445	74,7
Viscosity, 100 °C, mm <sup>2</sup> /s		12,4
Viscosity Index	ASTM D-2270	165
Pour Point, °C	ASTM D- 97	-33

\* Values shown may differ between productions.

