

MAXIMA M 5W-30

Fully Synthetic Engine Oil for Vehicles with Particulate Filter

Description

It is a new generation engine oil formulated with synthetic base oils and special additives, and produced for vehicles with emission reducing systems containing DPF and SCR.

Applications

Maxima M 5W-30 may be used in diesel passenger cars and light commercial vehicles requiring engine oil at the ACEA C2 or C3 performance level and equipped with exhaust emission systems containing DPF and SCR, and gasoline vehicles with catalytic converters. It is recommended not to use any additives along with this oil. Specially developed for Mitsubishi brand vehicles.

Benefits

- Provides high engine performance.
- Extends the life of exhaust emission systems.
- Protects the environment by contributing to low emission production.
- Helps keep the engine clean by reducing deposit and sediment formation.
- Supports fuel efficiency.

Performance

ACEA C2/C3-12, API SN

Typical Specifications*

SAE Viscosity Grade		5W-30
Density, @ 15 °C, kg/m ³	ASTM D-4052	0,85
Flash Point, COC, °C	ASTM D-92	230
Viscosity, 40 °C, mm ² /s	ASTM D 445	69,4
Viscosity, 100 °C, mm ² /s		11,6
Viscosity Index	ASTM D-2270	163
Pour Point, °C	ASTM D-97	-33

* Values shown may differ between productions.

