

MAXIMUS HD 10W-40

Ultra High Performance Diesel Engine Oil

Description

Engine oil formulated with advanced technology additives and premium quality synthetic base oils, developed for Euro V and Euro VI vehicles.

Applications

It is recommended for all heavy duty vehicles, construction equipment and highway fleet equipped with high power, 4-cycle diesel engines. It is convenient for engines with and without DPF and engines with EGR and SCR. It is especially recommended for modern Volvo Heavy Duty engines.

Benefits

- Protects the engine and particle filter by preventing excess friction and corrosion with its low-ash formulation.
- Reduces fuel consumption and extends drain intervals.
- Achieves piston cleanness by reducing piston deposit and residue.
- Protects the environment by exhaust emission control.

Performance

API CK-4/SN, ACEA E7/E9/E11, MB-Approval 228.31, VOLVO VDS-4.5, RENAULT TRUCKS RLD-3, MAN M3775, CUMMINS 20086, MTU Type 2.1, MACK EOS 4.5, JASO DH-2, CATERPILLAR ECF-3/ ECF-2/ECF-1-a, DEUTZ DQC III-18LA, DETROIT DIESEL DDC93K222

Typical Specifications*

SAE Viscosity Grade		10W-40
Density, 15 °C, kg/liter	ASTM D4052	0,858
Flash Point, COC, °C	ASTM D92	220
Viscosity, 40 °C, mm ² /s	ASTM D445	91,5
Viscosity, 100 °C, mm ² /s		13,90
Viscosity Index	ASTM D2270	153
Pour Point, °C	ASTM D97	-42

* Values shown may differ between productions.