

MAXIMUS HD 15W-40

Ultra High Performance Diesel Engine Oil

Description

Engine oil formulated with advanced technology additives and premium quality synthetic base oils, developed for Euro 5 and Euro 6 vehicles.

Applications

It is recommended for all heavy duty vehicles, construction equipment and highway fleet equipped with high power, 4-cycle diesel engines. It is convenient for engines with and without DPF and engines with EGR and SCR. It is especially recommended for modern Volvo Heavy Duty engines.

Benefits

- Protects the engine and particle filter by preventing excess friction and corrosion with its low-ash formulation.
- Reduces fuel consumption and extends drain intervals.
- Achieves piston cleanness by reducing piston deposit and residue.
- Protects the environment by exhaust emission control.

Performance

API CK-4/SN, ACEA E9-16, JASO DH-2, CAT ECF-3/ECF-2/ECF-1-a, Cummins 20086, Detroit Diesel DFS93K222, Deutz DQC III-10LA, Ford WSS-M2C171-F1, Mack EO-S-4.5, MAN M3775, MB-Approval 228.31, MTU Type 2.1, Renault Trucks RLD-4/3, Volvo VDS-4.5

Typical Specifications*

SAE Viscosity Grade		15W-40
Density, 15 °C, kg/liter	ASTM D4052	0,876
Flash Point, COC, °C	ASTM D92	220
Viscosity, 40 °C, mm ² /s	ASTM D445	113,4
Viscosity, 100 °C, mm ² /s		14,70
Viscosity Index	ASTM D2270	133
Pour Point, °C	ASTM D97	-33

* Values shown may differ between productions.